# **AUXILIARY HEATERS**



# RedDOT offers a variety of heaters to easily add to any application.



### MODEL: R-254

TYPE: AUXILIARY HEATER

- COMPACT SIZE, SIMPLE PLUMBING, AND HIGH OUTPUT
- IDEAL FOR ANY APPLICATION
- VERSATILE—MOUNTS IN ANY POSITION
- 16,000 BTU/HR @ 150 F AIR TEMP RISE
- 150 CFM
- AVAILABLE IN 12- OR 24-VOLT MODELS



MODEL: R-255 Type: Auxiliary heater

- COMPACT SIZE, SIMPLE PLUMBING, AND HIGH OUTPUT
- IDEAL FOR ANY APPLICATION
- VERSATILE—MOUNTS IN ANY POSITION
- 30,000 BTU/HR @ 100 F AIR TEMP RISE
- 280 CFM
- DOUBLE FAN
- AVAILABLE IN 12- OR 24-VOLT MODELS



#### MODEL: R-290

TYPE: AUXILIARY SINGLE-BLOWER HEATER

- MAXIMUM AIR VELOCITY
- ADDS THE POWER OF A THREE-SPEED MOTOR BLOWER TO RED DOT'S MOST COMPACT HEATER
- 20,000 BTU/HR @ 150 F AIR TEMP RISE
- 220 CFM
- AVAILABLE IN 12- OR 24-VOLT MODELS



MODEL: R-295

TYPE: AUXILIARY DOUBLE-BLOWER HEATER • 430 CFM

- 35 000 BTU/HR @ 1
- 35,000 BTU/HR @ 180 F AIR TEMP RISE
  MATES TWO THREE-SPEED MOTOR BLOWER ASSEMBLIES
- TO A COMPACT HEATER • AVAILABLE IN 12- OR 24-VOLT MODELS

# **AUXILIARY HEATERS**





## MODEL: R-3500

- TYPE: AUXILIARY HEATER
- HIGH-CAPACITY HEATER
- IDEAL FOR FIRE TRUCKS, RESCUE VEHICLES, AND BIG CABS
- LOW PROFILE
- TOUGH, RUGGED CONSTRUCTION
- 49,000 BTU/HR @ 180 F AIR TEMP RISE

• 480 CFM



### MODEL: R-6130

TYPE: BOX HEATER

- IDEAL FOR OFF-ROAD, CONSTRUCTION, AND BUS APPLICATIONS
- COMPACT SIZE MAKES IT EASY TO MOUNT IN TIGHT SPACES
- ROTATING BLOWER MAKES DUCTING EASY
- THREE-SPEED MOTOR
- 28,100 BTU/HR @ 180 F AIR TEMP RISE
- 283 CFM
- AVAILABLE IN 12- OR 24-VOLT MODELS



#### MODEL: R-3540 Type: Auxiliary Heater

- IDEAL FOR FIRE TRUCKS, BUSES, VANS
- PANCAKE FAN DESIGN MEANS QUIET OPERATION
- MOUNTS FLAT OR HORIZONTAL
- TOUGH, RUGGED CONSTRUCTION
- LOTS OF BTU FOR ITS SIZE: 22,970 BTU/HR @ 180 F AIR TEMP RISE
- 194 CFM
- VARIABLE SPEED CONTROL

DISTRIBUTED BY: